


PLAN



- ANCHOR BOLTS ARE AS PER IS : 2062, OR EQUIVALENT FY 250 mpa
- FOR LOCATION & REFERENCE POINT REFER ARCHITECTURAL DRAWING.
- STRUCTURAL STEEL SHALL CONFORM TO IS:2062
- WELDING SHALL CONFORM TO IS:816 & IS:9595. WELDING SYMBOLS AS PER IS:813.
- FABRICATION AND ERECTION SHALL CONFORM TO THE PROCEDURE DOWN IN IS:800.
- BOLTS AND NUTS SHALL CONFORM TO IS:1367, PROPERTY CLASS 8.8.
- ELECTRODES SHALL BE FROM APPROVED MANUFACTURER AND SHALL CONFORM TO IS:814.
- M.S. TUBES SHALL CONFORM TO IS:1239.
- ALL HOLLOW SECTION MEMBER SHALL BE OF FY 310 GRADE AN "I" BEAM CHANNEL, ANGLE SECTION SHALL BE FY 250 GRADE.
- ALL ERECTION BOLT 16 DIA FOR 180 DIA HOLES UNLESS OTHERWISE NOTED
- ALL WELD ARE 6MM MINIMUM TYPICAL U.N.O.

DATE :-
17-02-2016

PROJECT :-
RMI 6 CONVEYOR
STRUCTURE (RM16)

REV.	ISSUED	DATE
1	ISSUED FOR FABRICATION	17-02-2016

DRAWING :-
RMI-6 ERECTION LAYOUT & SECTION

SCALE :- 1:50
DRAWN :-
CHECKED :-
REVISION 1

CLIENT :-

ELECTROTECH
INDIA LTD. AHMEDABAD

ARCHITECT \ CONSULTANT :-
SILICON
ENGINEERING CONSULTANTS PVT LTD.
315 - Paldi Avenue, Opp. Grand Bhagwati,
S.S. Highway, Ahmedabad-380009, Gujarat, INDIA
e-mail: info@silicon.com
PH : +91-79-40201887
www.silicon.com

DRAWING NO :-
E001